

## INDEX G200

**Kind :** CNC lathe  
**Brand :** INDEX  
**Model :** G200  
**Year :** 2001  
**Serial Nr:** 511287  
**Stock Nr :** 10284



### TECHNICAL DETAILS

- Number of axes : 8
- Number of spindles : 2
- Number of turrets : 2
- MAIN SPINDLE
- Spindle nose : A2-5
- Spindle power : 22 [kW]
- Spindle speeds : 6000 [rpm]
- Max. bar diameter : 60 [mm]
- Max. turning diameter : 200 [mm]
- C axis indexing precision : 0.001 [°]
- COUNTER-SPINDLE
- Spindle nose : A2-5
- Spindle power : 22 [kW]
- Spindle speeds : 6000 [rpm]
- Max. bar diameter : 60 [mm]
- C axis indexing precision : 0.001 [°]
- Travel : 445 [mm]
- UPPER LEFT TURRET
- Number of positions : 14
- Number of motorized positions : 14
- X/Z stroke : 155/590 [mm]
- Y stroke : 120 [mm]
- Tool type : VDI 25
- Live tools speed : 6000 [rpm]

**Kind : CNC lathe**  
**Brand : INDEX**  
**Model : G200**  
**Year : 2001**  
**Serial Nr: 511287**  
**Stock Nr : 10284**

- Live tools power : 5.5 [kW]  
LOWER RIGHT TURRET  
- Number of positions : 14  
- Number of motorized positions : 14  
- X/Z stroke : 105/400 [mm]  
- Tool type : VDI 25  
- Live tools speed : 6000 [rpm]  
- Live tools power : 5.5 [kW]  
POWER SUPPLY  
- Supply voltage : 400 [V]  
- Total installed power : 39 [kW]  
WEIGHT & DIMENSIONS  
- Machine floor space : 4975 x 2890 [mm]  
- Machine height : 3269 [mm]  
- Machine weight : 5500 [kg]

#### **EQUIPMENT**

- CNC : INDEX C200-4 (Siemens 840C)  
- Interface : Ethernet / RS232 / USB / PCMCIA  
- Coolant tank : KNOLL  
- Chips conveyor : KNOLL  
- Oil mist extractor : FILTERMIST FX6000  
- Tool breakage detection  
- Parts catcher  
- Parts conveying strip  
- Bar loader : LNS hydrobar Sprint  
- Collet chuck : 2 x HAINBUCH